

CHAS. E. GOAD, LTD

CIVIL ENGINEERS

EXPLANATION OF SIGNS USED ON INSURANCE PLANS OF TOWNS & CITIES

56 CROUCH HILL

LONDON N.A.

ABBREVIATIONS

- ASB. ASBESTOS
- CORR. CORRUGATED IRON
- D.I.D. DOUBLE IRON DOORS
- DRA. DRAPERY
- D. DWELLING
- ELECT. ELECTRICIAN
- (E.M.) ELECTRIC MOTORS
- (ENG.) STEAM ENGINE
- FURNE. FURNITURE
- GAR. GARAGE
- (G.E.) GAS ENGINE
- H.W. HARDWARE
- I.COLS. IRON COLUMNS OR STEEL STANCHIONS
- JWLY. JEWELLERY
- M.CL. METAL CLAD
- M.W. MANCHESTER WAREHOUSE
- m.l. MATCH (OR WOOD) LINED
- OIL. OIL & COLOR
- (O.E.) OIL ENGINE
- P.H. PUBLIC HOUSE
- S. SHOP
- S.I.D. SINGLE IRON DOORS
- S.I.S. SINGLE IRON SHUTTERS
- TAI. TAILORS
- TENS. TENEMENTS
- W.G. WIRED GLASS
- W.N. WIRE NETTING OVER GLASS.

COLORS

- BRICK, STONE OR CONCRETE
- WOOD
- SKYLIGHTS ON 1 & 2 STORY BUILDINGS
- SKYLIGHTS ON HIGHER BUILDINGS
- METAL BUILDINGS.
- TIMBER PILED OR STACKED

WALLS

- PARTY WALL 2 STORIES OR OVER, A PROBABLE FIRE CUT OFF.
- ENTIRE WALL, BUT DOUBTFUL AS FIRE CUT OFF
- DEFECTIVE WALL - IMPERFECT
- WALL ABOVE, IRON COLS: UNDER
- WALL SOME FLOORS ONLY (OR WOOD OR PLASTER PARTITION)
- ABOVE ROOF 6" TO 1'-6"
- D^o — 1'-6" TO 2'-6"
- MATCH OR WOOD LINED
- WOOD CLAD WITH CORRUGATED IRON

OPENINGS

- PASSAGE UNDER
 - ON ALL FLOORS
 - SOME FLOORS ONLY
 - ALL FLOORS (PROTECTED)
 - ALL FLOORS (SOME PROTECTED)
 - SOME FLOORS ONLY (PROTECTED)
 - ALL FLOORS (SOME PROTECTED)
 - ALL FLOORS (PROTECTED)
 - SOME FLOORS ONLY (PROTECTED)
 - WOOD LOADING DOOR
 - IRON LOADING DOOR
- UNPROTECTED

SINGLE IRON DOORS

DOUBLE IRON DOORS

IRON SHUTTERS

SINGLE DOUBLE

S.I.S. D.I.S.

WINDOWS

- ON ALL OR MOST FLOORS
 - MORE THAN USUAL
 - OVERLOOKING
 - NEARLY ALL GLASS
 - OPENINGS THRO' & WINDOWS OVER
 - ON SOME FLOORS ONLY
 - PROTECTED BY WIRED GLASS
 - PROTECTED BY SINGLE IRON SHUTTERS
 - PROTECTED BY DOUBLE IRON SHUTTERS.
- WINDOWS IN FRONT & REAR OF BUILDINGS UNDERSTOOD
UNLESS OTHERWISE SHOWN

FLOORS

- 1.2.3.3½ &c ON BUILDINGS ARE NUMBER OF STORIES ABOVE GROUND
(3½=3 FLOORS & ATTIC)
- 2&2B MEANS 2 STORIES & 2 BASEMENTS BAST & SUB-BASEMENT.

SKYLIGHTS

- LESS THAN 50 SQUARE FEET (SAY 10'x5', OR 7'x7')
- OPENINGS THROUGH 2 FLOORS UNDER (EACH STROKE DENOTES AN OPENING.)
- WITH WELL HOLE THROUGH 3 FLOORS
- LANTERN LIGHT, SIDES ONLY GLASS. } OVER 50 SQ. FT. TO SCALE
- OR VENT. OR RAISED VENTILATOR


HOISTS & LIFTS

- OPEN OR ENCLOSED WOOD OR PLASTER
- OPEN WOOD FLAPS TO FLOORS
- ENCLOSED BRICK OR FIRE RESISTING IRON DOORS SHOWN AS EXPLAINED UNDER "OPENINGS"
- OPEN TO STREET
- ENCLOSED BRICK OR FIRE RESISTING WITH IRON SHUTTERS

ROOFS

- ASB ASBESTOS
- C CONCRETE
- CORR. CORRUGATED IRON
- T METAL
- P PATENT (FELT &c)
- O SLATE
- T TILE

PROFILES



SUNDRIES

- STEAM BOILERS
- BOILER SET IN BRICK
- FACTORY CHIMNEYS
- (ENG.) STEAM ENGINE
- OVERHANGING WOOD CORNICE
- FIRE ALARM BOX
- D^o ON KEY PLAN
- HYDRANT
- HYDRAULIC HYDRANT
- PRIVATE HYDRANT OR STAND PIPE
- DOUBLE HYDRANT
- SALT WATER HYDRANT
- SPRINKLER OR AUTO ALARM BELL

REFERENCE NUMBERS

- NUMBERS PARALLEL WITH STREET ARE EXISTING STREET N^{os}
- WHERE TWO SETS OF STREET N^{os} IN SAME BLOCK COINCIDE, ADDITIONAL ARBITRARY N^{os} ARE GIVEN TO ONE SET (500 & UPWARDS)
- WHERE BUILDINGS TO WHICH THEY APPLIED ARE DEMOLISHED, STREET & ARBITRARY N^{os} ARE SHOWN & CROSSED THROUGH ON REVISION
- 48' — ARE STREET WIDTHS.
- (37') ARE HEIGHTS OF GROUND ABOVE ORDNANCE DATUM.
- HEIGHT IN FEET OF ADJOINING BUILDINGS WHERE STORIES DIFFER IN HEIGHT
- SIZES OF WATER MAINS SUPPLYING HYDRANTS